LOW PROFILE LP RANGE

LP-SM8AS PRODUCT GUIDE

LP-SM8AS Surface Mount Male Adhesive Fix - 5kg

The LP-SM8AS is a male low profile clip with a surface mount installation. Featuring Fastmount's patented SuperGroove base, the grooves mechanically engage into the a 2 part epoxy to create a bond that supports a 5kg pull out load. Ideal for thin panels or panels where drilling into the surface is not possible. The clip also offers an option to screw fix directly through the head for rapid installation. Mounts into LP-F8, LP-DF8 and LP-AF8A female clips. Refer to Panel Offset Guide for gap between substrate and panel, pull out and shear loads.

LP-SM8AS

MATERIAL: White Acetal copolymer

USE WITH:





LP-DF8



MORE INFO: Installation Guide LP-F8 Clip Layout Guide TD-02, TD-08 Panel Offset Guide

BENEFITS

- No special tools required for installation
- · Adhesive or screw fix
- 5kg pull out load
- 4.3mm clearance between panel and substrate
- · CNC machine compatibility
- Acoustic isolation

APPLICATIONS

- · Thin wall panels
- · Lightweight ceiling panels
- · Covered, painted or prefinished panels
- Interior panels
- · Refit and upgrade work

INSTALLATION: Partially exploded through section showing typical installation method



