

STANDARD PC RANGE

PC-SM1AC PRODUCT GUIDE

PC-SM1AC Acoustic Surface Mount Male Adhesive Fix - 2kg

The PC-SM1AC surface mount male is designed for use with acoustic or extremely lightweight panels and has a 2kg pull out load. The acoustic male clip can be bonded to the panel using a 2 part epoxy or in the case of polyester fibre composition acoustic panels, hot melt glue. Compatible PC-F1A, PC-SF1 and PC-AF1. Refer to Panel Offset Guide for information about gap between substrate and panel, pull out and shear loads.

PC-SM1AC



USE WITH:

PC-F1A



PC-SF1



PC-AF1



MATERIAL:

Translucent Super flexible copolymer

MORE INFO:

Installation Guide PC-F1A, SF1, AF1
Clip Layout Guide TD-02, 09, 12
Panel Offset Guide

BENEFITS

- Self-aligning secure mounting (2kg pull out load)
- Installation requires no special tools
- Uses a 2 part epoxy or hot melt glue
- No drilling of panels
- Works with existing Fastmount female clips in the Standard Range
- Allows for flexing and expansion of panel and substrate frame
- Invisible fixings – no damage to face of panel
- Ability to remove and reinstall non-sequentially rapidly

APPLICATIONS

- Mounting extremely lightweight panels or acoustic panels
- Soft, low density panels - polyester fibre type, foam.
- Ideal for office retro-fits

INSTALLATION: Partially exploded through section showing typical installation method

