STANDARD PC RANGE PC-VM1 & PC-VMX PRODUCT GUIDE

PC-VM1 & PC-VMX Vario Clip Self Tapping male - 5 & 15kg

The self-tapping clip PC-VM1 and PC-VMX add to the Standard Range, offering 5kg and 15kg pull out loads respectively. Designed for variable gap, high shear strength applications. Variable gap measurements are 6.5mm at first engagement, 4mm at second engagement. Compatible with all female clips in the Standard Range.

PC-VM1







USE WITH: PC-F1A







PC-SF1





PC-AF1

MATERIAL:

White Acetal copolymer/GF Nylon Black Acetal copolymer/GF Nylon

MORE INFO:

Installation Guide PC-F1A, SF1, RF1 Clip Layout Guide TD-02, TD-08 Panel Offset Guide

BENEFITS

- Variable clipping depth
- · High shear load (See Panel Offset Guide)
- Remove and refit panels in any sequence multiple times
- Perfect panel alignment and secure mounting every time
- 5kg or 15kg pull out load per clip
- Durable design for frequent handling

APPLICATIONS

- · Seat backs and bases
- · Seat backs with removable covers
- Heavy wall panels
- Use in conjunction with Standard Range clips
- · Variety of substrates

INSTALLATION: Partially exploded through section showing typical installation method



