

# PANELSAFE PS RANGE


## PS-SR225SS PRODUCT GUIDE

### PS-SR225SS Seismount™ Stainless Steel – 225mm

The PanelSafe Seismount in stainless steel is a strong solution for high volume marine installations where added security and control of the panel is required. The Seismount allows the panel to be suspended below the ceiling for convenient servicing behind the panel or controlled removal of the panel. Install with M10 pan head screw or 6.3 x 8mm euro screw. Simply unhook the strap from the screws to remove the panel.

Drop length 225mm. 144kg break load for the PS-SR225SS in both wall and ceiling applications.

#### PS-SR225SS



#### USE WITH:

**PC** Standard Range  
**LP** Low Profile Range  
**VL** Very Low Profile Range  
**MC** Metal Range  
**SL** Stratlock Range

#### MATERIAL:

Silver Stainless steel

#### MORE INFO:

Installation Guide PS-SR225S

#### BENEFITS

- Low cost solution for high volume applications
- No special tools required for installation
- Install directly onto substrate face with screws
- Controlled removal of large panels
- Seismic security for overhead panels – prevents panels from falling
- Stainless steel composition for longevity in marine applications

#### APPLICATIONS

- Ceiling panels
- Wall panels
- Large panels
- Inspection and service panels

#### INSTALLATION: Partially exploded through section showing typical installation method

