












TEXTILE TC RANGE

TC-F6H & TC-M6 INSTALLATION GUIDE

TC-F6H & TC-M6 Textile Clip Range

| | | | |
|---|---|--|--|
| <p>TC-F6H</p>  | <p>TC-M6</p>  | <p>USE WITH:</p> <p>Upholstery sewing machine using standard foot, size 110/18 needle and V92 thread.</p> <p>#6 screw</p> | <p>INSTALL WITH:</p>  <p>TC-CP6H</p> |
|---|---|--|--|

INSTALLATION STEPS

| | | | |
|--|---|--|--|
| <p>1 Sew TC-F6H to fabric using 110/18 needle and V92 size thread along stitch groove.</p>  <p>TC-F6H</p> <p>Fabric</p> | <p>2 Complete cushion assembly.</p>  <p>Cushion</p> | <p>3 Insert TC-CP6H into TC-F6H. Press slider to hold TC-CP6 in place</p>  | <p>4 Align cushion and press firmly on mounting surface.</p>  |
| <p>5 Drill on mark.</p>  | <p>6 Screw TC-M6 onto base using #6 gauge CSK screw.</p>  | <p>7 Align cushion with TC-M6.</p>  | <p>7 Press cushion into place. To engage, slide lock away from cushion edge, to disengage, pull lock towards edge.</p>  |