

VERY LOW PROFILE VL RANGE

VL-03FR PRODUCT GUIDE

VL-03FR Very Low Profile Clip Set Fire Rated

The VL-03FR combines the Very Low Profile convenience for ceiling and wall panels, with a fire rating, making it useful in commercial areas where fire rating is required on thin panels. The VL-03FR can be rivet or screw fixed. Incorporates the patented SuperGroove® system. Tested to out-perform external screw fixings in fire rating testing using fire rated MDF with B Euroclass by CSTB*. *Scientific and Technical Centre for Building, France. Refer to Panel Offset Guide for gap between substrate and panel, pull out and shear loads.

BENEFITS

- Fire rated plastic with V-0 UL rating
- GWIT test at 2mm: 625°C, test method IEC-60695-2-13
- 10kg pull out load
- Rivet or screw fix to steel frames
- Screw fix to panels to ensure mechanical connection
- No special installation tools required

APPLICATIONS

- Fire rated ceiling and wall panels in areas with minimal frame and panel thickness
- Inspection panels
- Thin panels

VL-03FR

10kg



MATERIAL:

White Duranex

MORE INFO:

Installation Guide VL-03
Clip Layout Guide TD-02, 08, 09
Panel Offset Guide

INSTALLATION: Partially exploded through section showing typical installation method

