

STANDARD PC RANGE

PC-VM1 & PC-VMX PRODUCT GUIDE

PC-VM1 & PC-VMX Vario Clip Self Tapping male - 5 & 33lb

The self-tapping clip PC-VM1 and PC-VMX add to the Standard Range, offering 11lb and 33lb pull out loads respectively. Designed for variable gap, high shear strength applications. Variable gap measurements are 1/4" at first engagement, 5/32" at second engagement. Compatible with all female clips in the Standard Range.

PC-VM1



USE WITH:

PC-F1A

PC-RF1

PC-SF1

PC-AF1



PC-VMX 33lb



MATERIAL:

White Acetal copolymer/GF Nylon

Black Acetal copolymer/GF Nylon

MORE INFO:

Installation Guide PC-F1A, SF1, RF1

Clip Layout Guide TD-02, TD-08

Panel Offset Guide

BENEFITS

- Variable clipping depth
- High shear load (See Panel Offset Guide)
- Remove and refit panels in any sequence multiple times
- Perfect panel alignment and secure mounting every time
- 11lb or 33lb pull out load per clip
- Durable design for frequent handling

APPLICATIONS

- Seat backs and bases
- Seat backs with removable covers
- Heavy wall panels
- Use in conjunction with Standard Range clips
- Variety of substrates

INSTALLATION: Partially exploded through section showing typical installation method

