

# TEXTILE TC RANGE

## TC-CF3 PRODUCT GUIDE

### TC-CF3 Carpet Clip Female

The TC-CF3 is designed as a carpet clip for 0.12"-0.2" carpet that doesn't absorb heat from the sun, making it a superior alternative to metal studs that burn sailors' feet in marine applications. The TC-CF3 winds through a 5/8" hole punched into the carpet using the Fastmount CT-10 installation tool. The four wings tighten up onto the underside of the carpet holding it secure. Use with the TC-CSM6 on fiberglass or aluminum decks, or the stick-on TC-CSM6 can be used on a painted or fiberglass deck surface. The carpet is then clipped into place holding it secure. Use the CT-05 to lift the carpet off the male clip. 1' 3 3/4" max spacing recommended between clips.

Available in white, black, grey and clear.

#### TC-CF3



#### ! NEW

#### MATERIAL:

Polycarbonate

#### MORE INFO:

Installation Guide TC-CM6, TC-CSM6

#### USE WITH

TC-CM6



TC-CSM6



#### BENEFITS

- Quick and easy to install
- Cost-effective as minimal parts are required for fitting
- Protects skin from heat or burns where there is harsh exposure to sun
- Secures loose carpets to avoid trips or falls
- High quality, secure finish
- Designed as an improvement on traditional fixed methods
- Easy removal for cleaning, winterizing or replacement

#### APPLICATIONS

- Suitable for marine, architectural, aviation and RV
- Designed for 0.12"-0.2" carpet
- Interior and exterior fitted carpets
- Mats and loose fitting rugs
- Covers for machinery or outdoor furniture
- Refits and upgrades of existing installations

#### INSTALLATION:

